Please Click On Product Title To Go To The Product Page To Purchase

Rolls RA62c Headphone Amp

Six Channels of clean, quiet headphone/earphone amplification.
Individual Direct Inputs to mix separate stereo signal with Main Input signals.
1/4″ and 3.5mm Headphone/Earphone Outputs.
LED Clip indication.
Stereo/Mono operation.

Specifications
Input Impedance: 10K Ohms unbalanced
Max Input Level: 18 dBV
Input Connectors: 1/4″ TRS stereo, R & L bal. / unbal. 1/4″, RCA, R & L balanced XLR, 6: 1/4″ TRS Direct Input jacks
Output Connectors: 12: 1/4″ TRS Stereo jacks, 6: 1/8″ (3.5 mm) TRS Stereo jacks
Max Gain: 20 dB/Channel
Output Power: 972 mW/side, 1944 mW/Channel (@ 32 Ohms)
Frequency Response: DC – 30 kHz
S/N Ratio: 90 dB

THD: <.008%
IMD: <.008%
Phase Shift (In to Out): 0 deg.
Slew Rate: 25 V per microsecond Second
Crosstalk: – 65 dB
Power: 12 VAC (Rolls Model PS12)
Size: 19″ x 1.75″ x 6.5″ (48cm x 4.5cm x 17cm)
Weight: 7 lbs (3KG)

Price: $188.00

SKU: 5425

Categories: Rack Effects, Recording Equipment

Product Short Description :

The ROLLS RA62c is a six-channel headphone/earphone amplifier for professional audio monitoring. A variety of input options are available including 1/4″, RCA, and balanced XLR. Since the MONO/STEREO switch is after the pan control, it will mix 2 MONO signals and their balance can be adjusted with the Pan control. With the addition of rear panel Direct Input connectors, each channel may mix a second stereo signal.

Customer Service Is Our Top Priority!