

Rolls RA62c Headphone Amp

Six Channels of clean, quiet headphone/earphone amplification.
Individual Direct Inputs to mix separate stereo signal with
Main Input signals.

1/4" and 3.5mm Headphone/Earphone Outputs.

LED Clip indication.

Stereo/Mono operation.

Specifications

Input Impedance: 10K Ohms unbalanced

Max Input Level: 18 dBV

Input Connectors: 1/4" TRS stereo, R & L bal. / unbal. 1/4",
RCA, R & L balanced XLR, 6: 1/4" TRS Direct Input jacks

Output Connectors: 12: 1/4" TRS Stereo jacks, 6: 1/8" (3.5 mm)
TRS Stereo jacks

Max Gain: 20 dB/Channel

Output Power: 972 mW/side, 1944 mW/Channel (@ 32 Ohms)

Frequency Response: DC – 30 kHz

S/N Ratio: 90 dB

THD: <.008%

IMD: <.008%

Phase Shift (In to Out): 0 deg.

Slew Rate: 25 V per microsecond Second

Crosstalk: – 65 dB

Power: 12 VAC (Rolls Model PS12)

Size: 19" x 1.75" x 6.5" (48cm x 4.5cm x 17cm)

Weight: 7 lbs (3KG)