



Please Click The Product Title Link To See The Product Page, If You Would Like To Purchase.

[JBL PRX415M Passive Loudspeaker](#)



Features:

- 90° x 50° coverage
- Dual-angle pole socket for applications requiring tripod mounting
- Heavy Duty 16 gauge protective screen backed steel grille
- Tough DuraFlex™ enclosure finish
- SonicGuard™ protects the highfrequency driver from excess power without interrupting the performance.

Applications:

- Reinforcement of music and speech in entertainment, live or pre-recorded applications
- High-performance satellite speaker for use with subwoofers

Specifications:

Frequency Range (-10 dB): 55 Hz – 19 kHz

Frequency Response (+3 dB): 66 Hz – 16 kHz

Coverage Pattern: 90° x 50° nominal

System Sensitivity: 98 dB SPL (1w@1m)

Power Rating, Pink Noise: 300 W / 600 W / 1200 W
(Continuous/Program/Peak)

Rated Maximum SPL: 122 dB SPL cont. (129 dB SPL peak)

Nominal Impedance: 8 ohms

Dimensions (H x W x D): 650 mm x 429 mm x 457 mm (25.6" x 16.9" x 18")

Net Weight: 21 kg (46 lbs.)

[JBL PRX415M Data Sheet](#)

Price: \$739.00

SKU: 5210

Categories: [Live Sound & Lighting](#), [Loudspeakers](#)

Product Short Description :

PRX415M is a portable, fifteen-inch, two-way speaker system designed for either main sound reinforcement or monitoring applications.

Product Gallery:



Customer Service Is Our Top Priority!