Please Click On Categories Or Tags Link To Go To The Product Page To Purchase

JBL Control SB210-WH Passive Subwoofer

Features:

- 2 x 250 mm (10 in) Aluminum/ Ceramic Composite Cone Drivers.
- 400 W Power Handling.

- Fully Outdoor Capable Design.
- SonicGuard™ Overload Protection.
- 13 x M6 Suspension Inserts for Optional U-Bracket.
- AV Shielded.
- Compact, Low Profile Design.

Specifications:
Frequency Range: 42 Hz – 200 Hz (-10 dB)
Power Capacity: 800 W Continuous Program Power; 400 W Continuous Pink Noise
Nominal Sensitivity: 95 dB, 1 W @ 1 M in half space (2 in loading)
Frequency Response: 48 Hz – 120 Hz (± 3 dB)
Maximum SPL @ 1m: 122 dB (in half – space)
Nominal Impedance: 8 Ohms
Minimum Impedance: 7 Ohms at 100 Hz
Low Frequency: 2 x 250 mm (10 in) dia., 50 mm (2 in) edge wound ribbon voice coil, Aluminum/Ceramic Composite cone.
Enclosure Material: High Impact PolyStyrene (HIPS) w / internal 8 mm polyurethane co-mold.
Grille: Thermoset composite coated steel, multi-layer.
Overload Protection: SonicGuard™
Environmental: IEC 529 IP-X% rating. Exceeds MilSpec 810 for humidity, salt spray, temperature& UV. Passes Mil-STd-202F for salt spray.
Terminations: Screw-down terminal strips, zinc plated copper base, nickel-plated metal screw/washers. Accepts up to 9 mm outside, 4 mm inside open lug (#6, #8 or #10 lug), plus bare wire (up to AWG/2.5mm2).
Colors: Black or White (-WH)
Dimensions (H x W x D): 356 x 590 x 570 mm (14 x 23.3 x 22.5 in.)
Net Weight (ea): 17.1 kg (38 lb)
Shipping Weight (ea): 19.4 kg (43 lb)
Included Accessories: 1 pc MTC-PC4 input panel cover, 4 pcs MTC-210FT floor standing foot,4pcs MTC-210RT foot receptacle for stacking.

Optional Accessories: MTC-210UB U-Bracket
Accessories: 4MTTC-210-SAT stereo / mono high passing network with Satellite outputs MTC-210T mono network with transformers for 70.7/100V distributed line systems. Taps at 250 W, 125 W, 62 W (plus 31 W for 70.7V only). MTC-210T-SAT stereo/mono passing network with Satellite outputs and transformers for 70.7/100-Volt distributed line systems. Taps at 125 W, 62 W, 31 W (plus 15W for 70.7V only).

JBL SB210 Data Sheet

Price: $635.00

SKU: 4606

Categories: Live Sound & Lighting, Loudspeakers

Tags: Sub

Product Short Description :

Dual 10 in. Indoor/Outdoor High Output Compact Subwoofer
The Control SB210 provides low frequency reinforcement for a wide variety of sound system applications. Its compact size, high output and outdoor capable design makes it one of the most versatile subwoofers in the installation market.

Product Gallery:

Customer Service Is Our Top

Priority!