

Please Click On Product Title To Go To The Product Page To
Purchase

JBL JRX 215 15 Inch Passive Loudspeaker



Features:

• JBL 15 in low frequency driver with a 64 mm (2.5 in) diameter edgewound ribbon voice coil which provides more cross-sectional wire area in the voice coil gap than

round wire designs, for greater efficiency and power handling.

- JBL 2414H-C 25 mm (1 in) polymer diaphragm compression driver improves high frequency performance as well as system reliability.
- The advanced network topology crossover design shapes the frequency response to deliver coherent summation in the crossover region.
- High-voltage capacitors and inductors with massive cores and heavy gauge wire enable the crossover network to handle high power without saturating.
- Progressive Transition™ high frequency waveguide provides superior coverage control, reduced distortion, and smoother frequency response.
- The rugged, acoustically superior enclosure is constructed from 19 mm (.75 in) MDF (Medium Density Fiberboard) using advanced adhesives and mechanical fastener technology for extreme durability and improved low-frequency performance.
- SonicGuard™ protects the high frequency driver from excess power without interrupting the performance.
- Non-resonant, all-steel handles are used.
- Attractive 18-gauge perforated, steel grille protects components from damage.
- Dual-angle pole-mount socket allows the speakers to tilt
 10° for more uniform audience coverage.

Specifications:

Power Rating: 250 W / 1000W

Frequency Range (-10 dB): 41 Hz - 18 kHz Frequency Response (±3 dB): 59 Hz - 13 kHz

Sensitivity (@1m): 99 dB SPL (1w/1m)

Nominal Impedance: 8 ohms

Recommended Amplifier Power: 250 W to 500 W into 8 ohms

Maximum SPL: 129 dB

Nominal Dispersion: $90^{\circ} \times 50^{\circ}$ Crossover Frequency: 2.2 kHz

Dimensions (H \times W \times D): 699 mm \times 460 mm \times 432 mm (27.5 in \times

 $18.1 \text{ in } \times 17 \text{ in})$

Weight: 27.4 kg (60.5 lb)

driver mounted on Progressive Transition™ Waveguide

Low Frequency Driver: JBL M115-8A

Input Connectors: Neutrik® Speakon® NL-4 (x1); .25in TS phone

jack (x1); parallel

Price: \$399.00

SKU: 4716

Categories: <u>Live Sound & Lighting</u>, <u>Loudspeakers</u>

Tags: PA Speakers

Product Short Description:

Two-Way Sound Reinforcement Loudspeaker System
This trapezoidal, 15" speaker system is at home in live sound,
dance music and speech reinforcement.

Product Gallery:



Customer Service Is Our Top Priority!