

JBL JRX 215 15 Inch Passive Loudspeaker



Features:

- JBL 15 in low frequency driver with a 64 mm (2.5 in) diameter edgewound ribbon voice coil which provides more cross-sectional wire area in the voice coil gap than round wire designs, for greater efficiency and power handling.
- JBL 2414H-C 25 mm (1 in) polymer diaphragm compression driver improves high frequency performance as well as system reliability.
- The advanced network topology crossover design shapes the frequency response to deliver coherent summation in the crossover region.
- High-voltage capacitors and inductors with massive cores and heavy gauge wire enable the crossover network to handle high power without saturating.
- Progressive Transition™ high frequency waveguide provides superior coverage control, reduced distortion, and smoother frequency response.
- The rugged, acoustically superior enclosure is constructed from 19 mm (.75 in) MDF (Medium Density Fiberboard) using advanced adhesives and mechanical fastener technology for extreme durability and improved low-frequency performance.
- SonicGuard™ protects the high frequency driver from excess power without interrupting the performance.
- Non-resonant, all-steel handles are used.

- Attractive 18-gauge perforated, steel grille protects components from damage.
- Dual-angle pole-mount socket allows the speakers to tilt 10° for more uniform audience coverage.

Specifications:

Power Rating: 250 W / 1000W

Frequency Range (-10 dB): 41 Hz – 18 kHz

Frequency Response (± 3 dB): 59 Hz – 13 kHz

Sensitivity (@1m): 99 dB SPL (1w/1m)

Nominal Impedance: 8 ohms

Recommended Amplifier Power: 250 W to 500 W into 8 ohms

Maximum SPL: 129 dB

Nominal Dispersion: 90° x 50°

Crossover Frequency: 2.2 kHz

Dimensions (H x W x D): 699 mm x 460 mm x 432 mm (27.5 in x 18.1 in x 17 in)

Weight: 27.4 kg (60.5 lb)

High Frequency Driver: JBL 2414H-C , 1" exit compression driver mounted on Progressive Transition™ Waveguide

Low Frequency Driver: JBL M115-8A

Input Connectors: Neutrik® Speakon® NL-4 (x1); .25in TS phone jack (x1); parallel