Please Click On Product Title To Go To The Product Page To Purchase

Switchcraft 12A 1/4-Inch Female Panel-Mount Mono Jack With Shunt

Switchcraft 12A 1/4-Inch Female Panel-Mount Mono Jack w/Shunt

Life: Commercial Jacks – 10,000 insertion/withdrawal cycles, minimum.

Contact Resistance: Commercial Jacks – .030 ohms maximum (initial), .050 ohms maximum (after humidity, durability exposure).

Insulation Resistance: Commercial Jacks – 10,000 M(omega) minimum (initial), 1,000 M(omega) minimum (after humidity).

Dielectric Withstanding Voltage: 500 V, 60 Hz (rms) AC.

Contact Rating: 1 A, 25 V DC.

Thermal Range: Commercial Jacks; -55°C to +85°C (non-operating); -20°C to +65°C (operating).

Price: $19.99

SKU: 2433

Categories: Cable Parts & Adaptors

Product Short Description :

1/4-Inch Female Panel-Mount Mono Jack w/Shunt

2 conductor 1/4″ open frame jacks are ideal for musical instrument and speaker connections. Jacks mate with standard 1/4″ phone plugs and mount in a single 3/8″ diameter hole.

Customer Service Is Our Top Priority!