



Please Click The Product Title Link To See The Product Page, If You Would Like To Purchase.

## [Fisher Gold Bug Pro Metal Detector](#)



Mechanical: S-rod with electronics housing on rod, 3-piece breakdown construction, nonmetallic telescoping lower rod, adjustable position Armrest  
Weight: 2 lbs. 8 oz. with battery installed  
Standard searchcoil: 5 inch (12.7 cm) closed-frame round biaxial, waterproof  
Batteries: Single 9 volt rectangular alkaline Operating principle: VLF induction balance Operating frequency: 19 kHz, crystal controlled  
Reactive overload: 10,000 micro-cgs (with standard searchcoil)  
Resistive overload: 1,200 micro-cgs (with standard searchcoil)  
Ground balance range: From ferrite to salt water inclusive  
Discrimination ground suppression: Combination of 2nd and 3rd order methods  
Target-ID ground suppression: 3rd order  
Battery life: 15+ hours on good quality alkaline  
Operating temp range: 14 to 122 degrees F (-10 to +50 C) Operating humidity

range: 0 – 90% noncondensing

[Fisher Gold Bug Pro Metal Detector Manual](#)

**Price:** \$649.00

**SKU:** 7008

**Categories:** [Metal Detectors](#)

**Tags:** [Gold Detectors](#), [Gold Prospecting Supplies](#)

**Product Short Description :**

Finds the smallest gold nuggets in highly mineralized soils  
V-Break™ Industry's First Variable Breakpoint tone discrimination system  
Ground Grab®, Computerized Ground Balancing  
Real-Time computerized ground balancing  
V.C.O. Audio in All Metal & Discrimination Mode  
Independent control over Threshold & Gain  
Continuous Ground Condition Readouts  
Ground Phase value indicates type of mineralization  
Fe304 graphic indicates amount of mineralization  
Static Pinpoint with depth indicator  
Dual Headphone Jacks  
19kHz Operating Frequency  
Ultra-Simple User Interface  
Ultra-Lightweight (2.5 lbs.)  
Five Year Warranty

**Product Gallery:**



***Customer Service Is Our Top Priority!***