



Please Click On Product Title To Go To The Product Page To Purchase

Fisher Gold Bug Pro Metal Detector



Mechanical: S-rod with electronics housing on rod, 3-piece breakdown construction, nonmetallic telescoping lower rod, adjustable position Armrest

Weight: 2 lbs. 8 oz. with battery installed

Standard searchcoil: 5 inch (12.7 cm) closed-frame round biaxial, waterproof

Batteries: Single 9 volt rectangular alkaline Operating

principle: VLF induction balance Operating frequency: 19 kHz,
crystal controlled

Reactive overload: 10,000 micro-cgs (with standard searchcoil)

Resistive overload: 1,200 micro-cgs (with standard searchcoil)

Ground balance range: From ferrite to salt water inclusive

Discrimination ground suppression: Combination of 2nd and 3rd
order methods

Target-ID ground suppression: 3rd order

Battery life: 15+ hours on good quality alkaline

Operating temp range: 14 to 122 degrees F (-10 to +50 C)

Operating humidity range: 0 – 90% noncondensing

[Fisher Gold Bug Pro Metal Detector Manual](#)

Price: \$649.00

SKU: 7008

Categories: [Metal Detectors](#)

Tags: [Gold Detectors](#), [Gold Prospecting Supplies](#)

Product Short Description :

Finds the smallest gold nuggets in highly mineralized soils

V-Break™ Industry's First Variable Breakpoint tone
discrimination system

Ground Grab®, Computerized Ground Balancing

Real-Time computerized ground balancing

V.C.O. Audio in All Metal & Discrimination Mode

Independent control over Treshold & Gain

Continuous Ground Condition Readouts

Ground Phase value indicates type of mineralization

Fe304 graphic indicates amount of mineralization

Static Pinpoint with depth indicator

Dual Headphone Jacks

19kHz Operating Frequency

Ultra-Simple User Interface

Ultra-Lightweight (2.5 lbs.)

Five Year Warranty

Product Gallery:



**Customer Service Is Our Top
Priority!**