Please Click On Categories Or Tags Link To Go To The Product Page To Purchase

Fisher Gold Bug Pro Metal Detector



Mechanical: S-rod with electronics housing on rod, 3-piece breakdown construction, nonmetallic telescoping lower rod, adjustable position Armrest

Weight: 2 lbs. 8 oz. with battery installed

Standard searchcoil: 5 inch (12.7 cm) closed-frame round biaxial, waterproof

Batteries: Single 9 volt rectangular alkaline Operating

principle: VLF induction balance Operating frequency: 19 kHz, crystal controlled
Reactive overload: 10,000 micro-cgs (with standard searchcoil)
Resistive overload: 1,200 micro-cgs (with standard searchcoil)
Ground balance range: From ferrite to salt water inclusive
Discrimination ground suppression: Combination of 2nd and 3rd order methods
Target-ID ground suppression: 3rd order
Battery life: 15+ hours on good quality alkaline
Operating temp range: 14 to 122 degrees F (-10 to +50 C)
Operating humidity range: 0 – 90% noncondensing

Fisher Gold Bug Pro Metal Detector Manual

Price: $649.00

SKU: 7008

Categories: Metal Detectors

Tags: Gold Detectors, Gold Prospecting Supplies

Product Short Description :

Finds the smallest gold nuggets in highly mineralized soils
V-Break™ Industry's First Variable Breakpoint tone discrimination system
Ground Grab®, Computerized Ground Balancing
Real-Time computerized ground balancing
V.C.O. Audio in All Metal & Discrimination Mode
Independent control over Treshold & Gain
Continuous Ground Condition Readouts
Ground Phase value indicates type of mineralization
Fe3O4 graphic indicates amount of mineralization
Static Pinpoint with depth indicator
Dual Headphone Jacks
19kHz Operating Frequency
Ultra-Simple User Interface

Ultra-Lightweight (2.5 lbs.)
Five Year Warranty

Product Gallery:



Customer Service Is Our Top Priority!