**Please Click On Categories Or Tags Link To Go To The Product Page To Purchase**

# TASCAM US-1800 Computer Audio Interface



# US-1800 SPECIFICATIONS

| | |
|---|---|
| Supported sampling frequency | 44.1/48/88.2/96kHz |
| Supported bit rate | 16/24bit |
| Analog audio Inputs | |
| **MIC IN(1-8)** | XLR-3-31(1:GND, 2:HOT, 3:COLD), BALANCED |
| Input impedance | 2.2k ohms |
| Nominal input level | -2dBu |
| Minimum input level | -58dBu |
| Maximum input level | +14dBu |
| **GUITAR / LINE IN(9-10)** | |
| **GUITAR IN** | 6.3mm(1/4″) TS-jack(T:HOT, S:GND), UNBALANCED |
| Input impedance | 700k ohms |
| Nominal input level | -6dBV |
| Minimum input level | -52dBV |
| Maximum input level | +10dBV |
| **LINE IN** | 6.3mm(1/4″) TRS-jack(T:HOT, R:COLD, S:GND), BALANCED |

| | |
|---|---|
| Input impedance | 10k ohms |
| Nominal input level | +4dBu |
| Minimum input level | -42dBu |
| Maximum input level | +20dBu |
| **LINE IN(11-14)** | 6.3mm(1/4″) TRS-jack(T:HOT, R:COLD, S:GND), BALANCED |
| Input impedance | 10k ohms |
| Nominal input level | -10dBV/+4dBu |
| Maximum input level | +6dBV/+20dBu |
| Analog audio Outputs | |
| **LINE OUT(1-4)** | 6.3mm(1/4″) TRS-jack(T:HOT, R:COLD, S:GND), BALANCED |
| Output impedance | 100ohms |
| Nominal output level | +4dBu |
| Maximum output level | +24dBu |
| **MONITOR OUT(L/R)** | 6.3mm(1/4″) TRS-jack(T:HOT, R:COLD, S:GND), BALANCED |
| Output impedance | 100ohms |
| Nominal output level | +4dBu |

| | |
|---|---|
| Maximum output level | +24dBu |
| Digital audio Inputs | |
| COAXIAL | RCA pin-jack |
| Format | IEC60958-3(S/PDIF) |
| Input impedance | 75ohms |
| Level | 0.5Vp-p / 75ohms |
| Digital audio Outputs | |
| COAXIAL | RCA pin-jack |
| Format | IEC60958 Concumer(S/PDIF) and IEC958 Professional(AES/EBU)<br>*Selectable in the Control Panel betwiin |
| Output impedance | 75ohms |
| Level | 0.5Vp-p / 75ohms |
| PHONES | |
| Connector | 6.3mm(1/4″) stereo phone jack |
| Maximum output level | 50mW + 50mW(1kHz, 1%, 32ohms load) |
| **MIDI Input** | |
| Connector | DIN 5 pin |
| Format | Standard MIDI format |
| **MIDI Output** | |
| Connector | DIN 5 pin |
| Format | Standard MIDI format |
| **USB** | |
| Connector | USB B type 4pin |

| | |
|---|---|
| Format | USB2.0HIGH SPEED(480 MHz) |
| **Power** | AC100 – 240V, 50/60Hz(TASCAM PS-1225L, included) |
| **Power consumption** | 7.2W |
| **Dimensions** | 482.6(W)×44(H)×300.4(D)mm |
| **Weight** | 3.1kg |
| Operating temperature | 5-35˚C |
| **Bundle software** | Cubase LE |
| Accessories | AC adaptor(TASCAM PS-1225L), Power cord set for AC adaptor, CD-ROM (conataining driver), USB cable (1.5m), DVD-ROM (Cubase LE), Cubase LE quick start guide , Warranty card, Owner’s manual, Rack-mounting screw kit |

| **Audio performance** | |
|---|---|
| Frequency response | 20Hz to 20kHz, +/-1dB(44.1/48kHz, MIC IN – LINE OUT, minimum, JEITA)<br>20Hz to 40kHz, +1/-3dB(88.2/96kHz, MIC IN – LINE OUT minimum, JEITA) |
| S/N ratio | 96dB or more(44.1kHz, MIC IN – LINE OUT, GAIN knob set |
| THD | 0.01% or less(MIC IN – LINE OUT, GAIN knob set to |

| **Operating system requirem** | |
|---|---|
| | **Windows** |
| OS | Windows XP:32bit SP3 or mor<br>Windows Vista:32bit SP2 or mo<br>Windows 7:32bit<br>Windows 8:32bit |

| | |
|---|---|
| CPU | Pentium 4 1.4GHz or more, ADM |
| MEMORY | 1GB or mo |
| USB | USB2.0 |
| DRIVER | ASIO, WD |
| | **Macintosh** |
| OS | Mac OS X Leopard(10.5.6), Mac OS X Snow Leopard(10.6.8 |
| CPU | Intel Processor 1GHz or more, P |
| MEMORY | 1GB or mo |
| USB | USB2.0 |
| DRIVER | Core Audi |

**Price:** ~~$399.99~~ Original price was: $399.99.$349.99Current price is: $349.99.

**SKU:** 5987

**Categories:** Audio Interfaces, Recording Equipment

**Tags:** Computer Interface

**Product Short Description :**

## Discontinued

Please see the newer version TASCAM US-16X8 Computer-Tablet Audio Interface

The US-1800 audio interface from TASCAM offers 16 inputs and 4 outputs.  The US-1800 features eight XLR microphone inputs. Six balanced line inputs are also provided, as well as stereo S/PDIF digital and MIDI in and out.

Cubase LE5, the latest workstation software from Steinberg is included. This 48-track audio workstation includes must-have features like automation, plug-ins, mixing, editing and MIDI tracks.

If you want the most inputs into your computer for the minimum

amount of cash, TASCAM’s US-1800 is a great choice!

Stop by our retail store location for a discount!

**Product Gallery:**



# Customer Service Is Our Top Priority!