



Please Click On Product Title To Go To The Product Page To Purchase

# TASCAM US-1800 Computer Audio Interface



## US-1800 SPECIFICATIONS

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| Supported sampling frequency  | 44.1/48/88.2/96kHz                                   |
| Supported bit rate            | 16/24bit                                             |
| Analog audio Inputs           |                                                      |
| <b>MIC IN(1-8)</b>            | XLR-3-31(1:GND, 2:H0T, 3:COLD), BALANCED             |
| Input impedance               | 2.2k ohms                                            |
| Nominal input level           | -2dBu                                                |
| Minimum input level           | -58dBu                                               |
| Maximum input level           | +14dBu                                               |
| <b>GUITAR / LINE IN(9-10)</b> |                                                      |
| <b>GUITAR IN</b>              | 6.3mm(1/4") TS-jack(T:H0T, S:GND), UNBALANCED        |
| Input impedance               | 700k ohms                                            |
| Nominal input level           | -6dBV                                                |
| Minimum input level           | -52dBV                                               |
| Maximum input level           | +10dBV                                               |
| <b>LINE IN</b>                | 6.3mm(1/4") TRS-jack(T:H0T, R:COLD, S:GND), BALANCED |

|                         |                                                      |
|-------------------------|------------------------------------------------------|
| Input impedance         | 10k ohms                                             |
| Nominal input level     | +4dBu                                                |
| Minimum input level     | -42dBu                                               |
| Maximum input level     | +20dBu                                               |
| <b>LINE IN(11-14)</b>   | 6.3mm(1/4") TRS-jack(T:H0T, R:C0LD, S:GND), BALANCED |
| Input impedance         | 10k ohms                                             |
| Nominal input level     | -10dBV/+4dBu                                         |
| Maximum input level     | +6dBV/+20dBu                                         |
| Analog audio Outputs    |                                                      |
| <b>LINE OUT(1-4)</b>    | 6.3mm(1/4") TRS-jack(T:H0T, R:C0LD, S:GND), BALANCED |
| Output impedance        | 100ohms                                              |
| Nominal output level    | +4dBu                                                |
| Maximum output level    | +24dBu                                               |
| <b>MONITOR OUT(L/R)</b> | 6.3mm(1/4") TRS-jack(T:H0T, R:C0LD, S:GND), BALANCED |
| Output impedance        | 100ohms                                              |
| Nominal output level    | +4dBu                                                |

|                       |                                                                                                        |
|-----------------------|--------------------------------------------------------------------------------------------------------|
| Maximum output level  | +24dBu                                                                                                 |
| Digital audio Inputs  |                                                                                                        |
| COAXIAL               | RCA pin-jack                                                                                           |
| Format                | IEC60958-3(S/PDIF)                                                                                     |
| Input impedance       | 75ohms                                                                                                 |
| Level                 | 0.5Vp-p / 75ohms                                                                                       |
| Digital audio Outputs |                                                                                                        |
| COAXIAL               | RCA pin-jack                                                                                           |
| Format                | IEC60958 Consumer(S/PDIF) and IEC958 Professional(AES/EBU)<br>*Selectable in the Control Panel betwiin |
| Output impedance      | 75ohms                                                                                                 |
| Level                 | 0.5Vp-p / 75ohms                                                                                       |
| PHONES                |                                                                                                        |
| Connector             | 6.3mm(1/4") stereo phone jack                                                                          |
| Maximum output level  | 50mW + 50mW(1kHz, 1%, 32ohms load)                                                                     |
| <b>MIDI Input</b>     |                                                                                                        |
| Connector             | DIN 5 pin                                                                                              |
| Format                | Standard MIDI format                                                                                   |
| <b>MIDI Output</b>    |                                                                                                        |
| Connector             | DIN 5 pin                                                                                              |
| Format                | Standard MIDI format                                                                                   |
| <b>USB</b>            |                                                                                                        |
| Connector             | USB B type 4pin                                                                                        |

|                              |                                                                                                                                                                                                                     |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Format</b>                | USB2.0HIGH SPEED(480 MHz)                                                                                                                                                                                           |
| <b>Power</b>                 | AC100 – 240V, 50/60Hz(TASCAM PS-1225L, included)                                                                                                                                                                    |
| <b>Power consumption</b>     | 7.2W                                                                                                                                                                                                                |
| <b>Dimensions</b>            | 482.6(W)×44(H)×300.4(D)mm                                                                                                                                                                                           |
| <b>Weight</b>                | 3.1kg                                                                                                                                                                                                               |
| <b>Operating temperature</b> | 5-35°C                                                                                                                                                                                                              |
| <b>Bundle software</b>       | Cubase LE                                                                                                                                                                                                           |
| <b>Accessories</b>           | AC adaptor(TASCAM PS-1225L), Power cord set for AC adaptor, CD-ROM (containing driver), USB cable (1.5m), DVD-ROM (Cubase LE), Cubase LE quick start guide , Warranty card, Owner's manual, Rack-mounting screw kit |

| <b>Audio performance</b>  |                                                                                                                                               |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Frequency response</b> | 20Hz to 20kHz, +/-1dB(44.1/48kHz, MIC IN – LINE OUT, minimum, JEITA)<br>20Hz to 40kHz, +1/-3dB(88.2/96kHz, MIC IN – LINE OUT, minimum, JEITA) |
| <b>S/N ratio</b>          | 96dB or more(44.1kHz, MIC IN – LINE OUT, GAIN knob set to 0)                                                                                  |
| <b>THD</b>                | 0.01% or less(MIC IN – LINE OUT, GAIN knob set to 0)                                                                                          |

| <b>Operating system requirements</b> |                                                                                                       |
|--------------------------------------|-------------------------------------------------------------------------------------------------------|
| <b>Windows</b>                       |                                                                                                       |
| <b>OS</b>                            | Windows XP:32bit SP3 or more<br>Windows Vista:32bit SP2 or more<br>Windows 7:32bit<br>Windows 8:32bit |

|                  |                                                        |
|------------------|--------------------------------------------------------|
| CPU              | Pentium 4 1.4GHz or more, ADM                          |
| MEMORY           | 1GB or mo                                              |
| USB              | USB2.0                                                 |
| DRIVER           | ASIO, WDI                                              |
| <b>Macintosh</b> |                                                        |
| OS               | Mac OS X Leopard(10.5.6), Mac OS X Snow Leopard(10.6.8 |
| CPU              | Intel Processor 1GHz or more, P                        |
| MEMORY           | 1GB or mo                                              |
| USB              | USB2.0                                                 |
| DRIVER           | Core Audi                                              |

**Price:** ~~\$399.99~~ Original price was: \$399.99.~~\$349.99~~Current price is: \$349.99.

**SKU:** 5987

**Categories:** [Audio Interfaces](#), [Recording Equipment](#)

**Tags:** [Computer Interface](#)

**Product Short Description :**

## Discontinued

Please see the newer version [TASCAM US-16X8 Computer-Tablet Audio Interface](#)

The US-1800 audio interface from TASCAM offers 16 inputs and 4 outputs. The US-1800 features eight XLR microphone inputs. Six balanced line inputs are also provided, as well as stereo S/PDIF digital and MIDI in and out.

Cubase LE5, the latest workstation software from Steinberg is included. This 48-track audio workstation includes must-have features like automation, plug-ins, mixing, editing and MIDI tracks.

If you want the most inputs into your computer for the minimum

amount of cash, TASCAM's US-1800 is a great choice!

Stop by our retail store location for a discount!

**Product Gallery:**



**Customer Service Is Our Top  
Priority!**