



Please Click On Product Title To Go To The Product Page To  
Purchase

# **TASCAM US-2X2 Computer-Tablet Audio Interface**



|                                    | US-       |
|------------------------------------|-----------|
| Sampling frequency                 |           |
| Quantization bit rate              |           |
| Analog audio inputs                |           |
| <b>MIC IN</b>                      | <b>IN</b> |
| Connector                          | XLR-3-31  |
| Input impedance                    |           |
| Nominal input level                |           |
| GAIN:MAX                           |           |
| GAIN:MIN                           |           |
| Maximum input level<br>(GAIN:MIN ) |           |

|                                    |                                  |
|------------------------------------|----------------------------------|
| Gain                               |                                  |
| <b>INST IN</b>                     | IN                               |
| Connector                          | 6.3mm (1/4")<br>(When set        |
| Input impedance                    |                                  |
| Nominal input level                |                                  |
| GAIN:MAX                           |                                  |
| GAIN:MIN                           |                                  |
| Maximum input level<br>(GAIN:MIN ) |                                  |
| Gain                               |                                  |
| <b>LINE IN</b>                     | IN                               |
| Connector                          | 6.3mm (1/4") TRS<br>(When set to |
| Input impedance                    |                                  |
| Nominal input level                |                                  |
| GAIN:MAX                           |                                  |
| GAIN:MIN                           |                                  |
| Maximum input level<br>(GAIN:MIN ) |                                  |
| Gain                               |                                  |
| Analog audio outputs               |                                  |
| <b>LINE OUT</b>                    |                                  |
| Connector                          | 6.3mm (1/4") TRS                 |
| Output impedance                   |                                  |
| Nominal output level               |                                  |
| Maximum output level               |                                  |
| <b>PHONES</b>                      |                                  |
| Connector                          | 6.3                              |

|                            |                                                |
|----------------------------|------------------------------------------------|
| Maximum output level       | 18mW+18mW<br>(THD+N 0.1% or less)              |
| MIDI IN / OUT              |                                                |
| Connector                  |                                                |
| Format                     |                                                |
| USB                        |                                                |
| Connector                  |                                                |
| Format                     |                                                |
| Power                      |                                                |
| When connected PC          | USB bus                                        |
| When connected iOS         | AC Adapter<br>(TASCAM PS-P520, ...)            |
| Power consumption          | 2.1W                                           |
| Dimensions                 | 7.32" W x 2.5" H<br>(186mm W x 65mm H)         |
| Weight                     | 2.43lb                                         |
| Operating temperature      |                                                |
| Bundled software           |                                                |
| Accessories                | USB cable, SONAR X3 LE license card, Live 9 LE |
| <b>Audio performance</b>   |                                                |
| Frequency response         |                                                |
| <b>LINE OUT (BALANCED)</b> |                                                |
| 44.1k/48k Hz               | 20Hz to 20kHz, +0dB/-0.1dB                     |
| 88.2k/96k Hz               | 20Hz to 40kHz, +0dB/-0.2dB                     |
| <b>PHONES</b>              |                                                |
| 44.1k/48k Hz               | 20Hz to 20kHz, +0dB/-0.5dB                     |
| 88.2k/96k Hz               | 20Hz to 40kHz, +0dB/-2dB                       |
| THD                        | 0.003% or less                                 |
| <b>S/N ratio</b>           | 101dB or more                                  |

|                        |                                                         |
|------------------------|---------------------------------------------------------|
| Crosstalk              | 95dB or more                                            |
| EIN                    | -127dBu or less                                         |
| <b>Computer system</b> |                                                         |
| <b>Windows</b>         |                                                         |
| OS                     | Windows 7(32-bit SP1, 64-bit SP1), Windows 8.0 or later |
| Compatible computers   | Windows-compatible                                      |
| CPU type/speed         | Dual-core or higher                                     |
| Memory                 | 4GB or more                                             |
| DRIVER                 |                                                         |
| <b>Macintosh</b>       |                                                         |
| OS                     | OS X Mountain Lion(10.8), OS X Mavericks(10.9)*         |
| Compatible computers   | Apple Macintosh                                         |
| CPU type/speed         | Dual-core or higher                                     |
| Memory                 | 4GB or more                                             |
| DRIVER                 |                                                         |
| <b>iOS</b>             |                                                         |
| OS                     | iOS 7* For more information about                       |

UPC 043774031009

**Price:** \$189.99

**SKU:** 6722

**Categories:** [Audio Interfaces](#), [Recording Equipment](#)

**Tags:** [Computer Interface](#)

### Product Short Description :

2-in/2-out Audio/MIDI Interface with HDDA Mic Preamps and iOS Compatibility

TASCAM's US-2x2 combines great audio quality and ergonomic

design for a powerful 2-in/2-out USB 2 Audio interface.

Two of TASCAM's Ultra-HDDA mic/line preamps provide up to 57dB of gain with nearly inaudible noise and distortion specs. The audio design features high-performance, musical components like NE5532 op amps for rich sound quality without coloring the source.

The US-2x2 includes class-compliant drivers for plug-and-play operation on Mac OSX and iOS devices like the iPad, and a simple driver adds ASIO compatibility for Windows. MIDI in and out are also included for connecting synths, drum machines, and controllers. The interface includes two DAW applications to choose from – both Cakewalk SONAR X3 LE and Ableton Live Lite 9.

With solid audio specs, iOS compatibility, and an easy-to-read angled design, the US-2x2 is the ultimate 2-channel interface for home, project, and mobile studios.

### **Product Gallery:**



**Customer Service Is Our Top  
Priority!**