



Please Click On Product Title To Go To The Product Page To
Purchase

TASCAM US-2X2 Computer-Tablet Audio Interface



	US-
Sampling frequency	
Quantization bit rate	
Analog audio inputs	
MIC IN	IN
Connector	XLR-3-31
Input impedance	
Nominal input level	
GAIN:MAX	
GAIN:MIN	
Maximum input level (GAIN:MIN)	

Gain	
INST IN	IN
Connector	6.3mm (1/4") (When set
Input impedance	
Nominal input level	
GAIN:MAX	
GAIN:MIN	
Maximum input level (GAIN:MIN)	
Gain	
LINE IN	IN
Connector	6.3mm (1/4") TRS (When set to
Input impedance	
Nominal input level	
GAIN:MAX	
GAIN:MIN	
Maximum input level (GAIN:MIN)	
Gain	
Analog audio outputs	
LINE OUT	
Connector	6.3mm (1/4") TRS
Output impedance	
Nominal output level	
Maximum output level	
PHONES	
Connector	6.3

Maximum output level	18mW+18mW (THD+N 0.1% or less)
MIDI IN / OUT	
Connector	
Format	
USB	
Connector	
Format	
Power	
When connected PC	USB bus
When connected iOS	AC Adapter (TASCAM PS-P520, etc.)
Power consumption	2.5W
Dimensions	7.32" W ×2.55" H (186mm W × 65mm H)
Weight	2.43lb
Operating temperature	
Bundled software	
Accessories	USB cable, SONAR X3 LE license card, Live 9 LE
Audio performance	
Frequency response	
LINE OUT (BALANCED)	
44.1k/48k Hz	20Hz to 20kHz, +0dB/-0.1dB
88.2k/96k Hz	20Hz to 40kHz, +0dB/-0.2dB
PHONES	
44.1k/48k Hz	20Hz to 20kHz, +0dB/-0.5dB
88.2k/96k Hz	20Hz to 40kHz, +0dB/-2dB
THD	0.003% or less
S/N ratio	101dB or more

Crosstalk	95dB or more
EIN	-127dBu or less
Computer system	
Windows	
OS	Windows 7(32-bit SP1, 64-bit SP1), Windows 8.0 or later
Compatible computers	Windows-compatible
CPU type/speed	Dual-core or higher
Memory	4GB or more
DRIVER	
Macintosh	
OS	OS X Mountain Lion(10.8), OS X Mavericks(10.9)*
Compatible computers	Apple Macintosh
CPU type/speed	Dual-core or higher
Memory	4GB or more
DRIVER	
iOS	
OS	iOS 7* For more information about iOS 7, please visit the Apple website.

UPC 043774031009

Price: \$189.99

SKU: 6722

Categories: [Audio Interfaces](#), [Recording Equipment](#)

Tags: [Computer Interface](#)

Product Short Description :

2-in/2-out Audio/MIDI Interface with HDDA Mic Preamps and iOS Compatibility

TASCAM's US-2x2 combines great audio quality and ergonomic

design for a powerful 2-in/2-out USB 2 Audio interface.

Two of TASCAM's Ultra-HDDA mic/line preamps provide up to 57dB of gain with nearly inaudible noise and distortion specs. The audio design features high-performance, musical components like NE5532 op amps for rich sound quality without coloring the source.

The US-2x2 includes class-compliant drivers for plug-and-play operation on Mac OSX and iOS devices like the iPad, and a simple driver adds ASIO compatibility for Windows. MIDI in and out are also included for connecting synths, drum machines, and controllers. The interface includes two DAW applications to choose from – both Cakewalk SONAR X3 LE and Ableton Live Lite 9.

With solid audio specs, iOS compatibility, and an easy-to-read angled design, the US-2x2 is the ultimate 2-channel interface for home, project, and mobile studios.

Product Gallery:



**Customer Service Is Our Top
Priority!**