



Please Click The Product Title Link Below To See The Product If You Would Like To Purchase.

[\*\*TASCAM US-2X2 Computer-Tablet Audio\*\*](#)

# Interface

	<b>US-2x2</b>
Sampling frequency	44.1k/48k/88.2k/96k/192k
Quantization bit rate	16/24bit
Analog audio inputs	
<b>MIC IN</b>	IN 1-2
Connector	XLR-3-31(1:GND, 2:HOT, 3:COLD)
Input impedance	2.2k ohm
Nominal input level	
GAIN:MAX	-65dBu (0.003V)
GAIN:MIN	-8dBu (0.309V)
Maximum input level (GAIN:MIN )	+8dBu (1.94V)
Gain	57dB
<b>INST IN</b>	IN 1-2
Connector	6.3mm(1/4")TS-jack(T□HOT, R□COLD) (When set to "INST" at MENU)
Input impedance	1M ohm
Nominal input level	
GAIN:MAX	-63dBV(0.003V)
GAIN:MIN	-6dBV(0.501V)
Maximum input level (GAIN:MIN )	+10dBV(3.16V)
Gain	57dB
<b>LINE IN</b>	IN 1-2
Connector	6.3mm(1/4")TRS-jack(T□HOT, R□COLD) (When set to "MIC/LINE" at MENU)
Input impedance	10k ohm
Nominal input level	
GAIN:MAX	-53dBu(0.003V)
GAIN:MIN	+4dBu(1.228V)
Maximum input level (GAIN:MIN )	+20dBu(7.746V)
Gain	57dB
Analog audio outputs	
<b>LINE OUT</b>	
Connector	6.3mm(1/4")TRS-jack(T□HOT, R□COLD)
Output impedance	110ohm
Nominal output level	+4dBu (1.228V)
Maximum output level	+20dBu (7.746V)
<b>PHONES</b>	
Connector	6.3mm(1/4") stereo
Maximum output level	18mW+18mW or more (THD+N 0.1% or less, 32ohms loaded)
<b>MIDI IN / OUT</b>	
Connector	Din 5-pin
Format	Standard MIDI
<b>USB</b>	
Connector	USB B type
Format	USB2.0 HIGH SPEED
Power	
When connected PC	USB bus powered
When connected iOS	AC Adapter (TASCAM PS-P520, sold separately)

Power consumption	2.5W
Dimensions	7.32" W x 2.56" H x 6.3" D (186mm W x 65mm H x 160mm D)
Weight	2.43lb (1.1kg)
Operating temperature	5 to 35
Bundled software	Cakewalk SONAR Ableton Live
Accessories	USB cable, SONAR X3 LE license card, Live 9 Lite license card,

### Audio performance

#### Frequency response

#### LINE OUT (BALANCED)

44.1k/48k Hz 20Hz to 20kHz, +0dB/-0.1dB

88.2k/96k Hz 20Hz to 40kHz, +0dB/-0.2dB

#### PHONES

44.1k/48k Hz 20Hz to 20kHz, +0dB/-0.5dB

88.2k/96k Hz 20Hz to 40kHz, +0dB/-2dB

THD 0.003% or less

S/N ratio 101dB or more

Crosstalk 95dB or more

EIN -127dBu or less

### Computer system requirements

#### Windows

OS Windows 7(32-bit SP1, 64-bit SP1), Windows 8.0(32-bit, 64-bit),  
of the latest OS version, please click [here](#).

Compatible computers Windows-compatible computer with a USB 2.0 port

CPU type/speed Dual core/2 GHz or faster (x86)

Memory 2GB or more

DRIVER ASIO2.0, WDM(MME)

#### Macintosh

OS OS X Mountain Lion(10.8), OS X Mavericks(10.9)\* For further info

Compatible computers Apple Macintosh computer with a USB 2.0 port

CPU type/speed Dual core/2 GHz or faster

Memory 2GB or more

DRIVER Core Audio, Core MIDI

#### iOS

OS iOS 7\* For more information about the OS compatibility on each m

UPC 043774031009

**Price:** \$179.99

**SKU:** 6722

**Categories:** [Audio Interfaces](#), [Recording Equipment](#)

**Tags:** [Computer Interface](#)

### Product Short Description :

2-in/2-out Audio/MIDI Interface with HDDA Mic Preamps and iOS Compatibility

TASCAM's US-2x2 combines great audio quality and ergonomic design for a powerful 2-in/2-out USB 2 Audio interface.

Two of TASCAM's Ultra-HDDA mic/line preamps provide up to 57dB of gain with nearly inaudible noise and distortion specs. The audio design features high-performance, musical components like NE5532 op amps for rich sound quality without coloring the source.

The US-2x2 includes class-compliant drivers for plug-and-play operation on Mac OSX and iOS devices like the iPad, and a simple driver adds ASIO compatibility for Windows. MIDI in and out are also included for connecting synths, drum machines, and controllers. The interface includes two DAW applications to choose from – both Cakewalk SONAR X3 LE and Ableton Live Lite 9.

With solid audio specs, iOS compatibility, and an easy-to-read angled design, the US-2x2 is the ultimate 2-channel interface for home, project, and mobile studios.

### **Product Gallery:**



***Customer Service Is Our Top Priority!***