

Please Click On Product Title To Go To The Product Page To
Purchase

TASCAM US-2X2 Computer-Tablet Audio Interface



	US-
Sampling frequency	
Quantization bit rate	
Analog audio inputs	
MIC IN	IN
Connector	XLR-3-31
Input impedance	
Nominal input level	
GAIN: MAX	
GAIN:MIN	
Maximum input level (GAIN:MIN)	

Gain	
INST IN	IN
Connector	6.3mm(1/4"
	(When set
Input impedance	
Nominal input level	
GAIN:MAX	
GAIN:MIN	
Maximum input level	
(GAIN:MIN)	
Gain	
LINE IN	IN
Connector	6.3mm(1/4")TRS
	(When set to
Input impedance	
Nominal input level	
GAIN: MAX	
GAIN:MIN	
Maximum input level	
(GAIN:MIN)	
Gain	
Analog audio outputs	
LINE OUT	
Connector	6.3mm(1/4")TR
Output impedance	
Nominal output level	
Maximum output level	
PHONES	
Connector	6.3

Maximum output leve	18mW+18mW (THD+N 0.1% or les	
MIDI IN / OUT	(111D+N 0.1% 01 Ces	
Connector		
Format		
USB		
Connector		
Format		
Power		
When connected PC	USB bus	
When connected iOS	AC Ad	
	(TASCAM PS-P520,	
Power consumption	2.	
Dimensions	7.32″ W ×2.5	
	(186mm W x 65m	
Weight	2.43lb	
Operating temperatu	re	
Bundled software		
Accessories	USB cable, SONAR X3 LE license card, Live 9 Li	
Audio performance		
Frequency response		
LINE OUT (BALANCED)		
44.1k/48k Hz	20Hz to 20kHz, +0dB/-0.1dB	
88.2k/96k Hz	20Hz to 40kHz, +0dB/-0.2dB	
PHONES		
44.1k/48k Hz	20Hz to 20kHz, +0dB/-0.5dB	
88.2k/96k Hz	20Hz to 40kHz, +0dB/-2dB	
THD	0.003% or less	
S/N ratio	101dB or more	

EIN	-127dBu or less
	Computer syst
	Wi
0S	Windows 7(32-bit SP1, 64-bit SP1), Windows 8.0 of the late
Compatible computers	Windows-comp
CPU type/speed	Dual
Memory	
DRIVER	
	Мас
0S	OS X Mountain Lion(10.8), OS X Mavericks(10.9)
Compatible computers	Apple Maci
CPU type/speed	
Memory	
DRIVER	
0S	iOS 7* For more information ab

95dB or more

UPC 043774031009

Crosstalk

Price: \$189.99

SKU: 6722

Categories: Audio Interfaces, Recording Equipment

Tags: Computer Interface

Product Short Description:

2-in/2-out Audio/MIDI Interface with HDDA Mic Preamps and iOS Compatibility

TASCAM's US-2×2 combines great audio quality and ergonomic

design for a powerful 2-in/2-out USB 2 Audio interface.

Two of TASCAM's Ultra-HDDA mic/line preamps provide up to 57dB of gain with nearly inaudible noise and distortion specs. The audio design features high-performance, musical components like NE5532 op amps for rich sound quality without coloring the source.

The US-2×2 includes class-compliant drivers for plug-and-play operation on Mac OSX and iOS devices like the iPad, and a simple driver adds ASIO compatibility for Windows. MIDI in and out are also included for connecting synths, drum machines, and controllers. The interface includes two DAW applications to choose from — both Cakewalk SONAR X3 LE and Abelton Live Lite 9.

With solid audio specs, iOS compatibility, and an easy-to-read angled design, the US-2×2 is the ultimate 2-channel interface for home, project, and mobile studios.

Product Gallery:



Customer Service Is Our Top Priority!