



Please Click The Product Title Link To See The Product Page, If You Would Like To Purchase.

[TASCAM US-4X4 Computer-Tablet Audio Interface](#)



Sampling frequency
Quantization bit rate
Analog audio inputs

US-4x4

MIC IN	IN 1-4
Connector	XLR-3-31
Input impedance	
Nominal input level	
GAIN:MAX	
GAIN:MIN	
Maximum input level	
(GAIN:MIN)	
Gain	
INST IN	IN 1-2
Connector	6.3mm(1/4")
	(When set
Input impedance	
Nominal input level	
GAIN:MAX	
GAIN:MIN	
Maximum input level	
(GAIN:MIN)	
Gain	
LINE IN	IN 1-4
Connector	6.3mm(1/4") TRS
	(When set to
Input impedance	
Nominal input level	
GAIN:MAX	
GAIN:MIN	
Maximum input level	
(GAIN:MIN)	
Gain	
Analog audio outputs	
LINE OUT	
Connector	6.3mm(1/4") TRS
Output impedance	
Nominal output level	
Maximum output level	
PHONES	
Connector	6.3
Maximum output level	45mW+45mW o
	(THD+N 0.1% or less,
MIDI IN / OUT	
Connector	
Format	
USB	
Connector	
Format	
Power	
When connected PC	
When connected iOS	
Power consumption	5W
Dimensions	11.62" W x 2.56"
	(296mm W x65mm H
Weight	3.53lb (1.6
Operating temperature	
Bundled software	
Accessories	AC adapter(GPE248-120200-Z), USB cable, SONAR X3 LE license card

Audio performance

Frequency response

LINE OUT (BALANCED)

44.1k/48k Hz

20Hz to 20kHz, +0dB/-0.1dB

88.2k/96k Hz

20Hz to 40kHz, +0dB/-0.2dB

PHONES

44.1k/48k Hz

20Hz to 20kHz, +0dB/-0.5dB

88.2k/96k Hz

20Hz to 40kHz, +0dB/-2dB

THD

0.003% or less

S/N ratio

101dB or more

Crosstalk

95dB or more

EIN

-127dBu or less

Computer system requirements

Windows

OS Windows 7(32-bit SP1, 64-bit SP1), Windows 8.0(32-bit, 64-bit), of the latest OS version, please click [here](#).

Compatible computers Windows-compatible computer with a USB 2.0 port

CPU type/speed Dual core/2 GHz or faster (x86)

Memory 2GB or more

DRIVER ASIO2.0, WDM(MME)

Macintosh

OS OS X Mountain Lion(10.8), OS X Mavericks(10.9)* For further info

Compatible computers Apple Macintosh computer with a USB 2.0 port

CPU type/speed Dual core/2 GHz or faster

Memory 2GB or more

DRIVER Core Audio, Core MIDI

iOS

OS iOS 7* For more information about the OS compatibility on each m

UPC 043774031016

Price: \$249.99

SKU: 7000

Categories: [Audio Interfaces](#), [Recording Equipment](#)

Tags: [Computer Interface](#)

Product Short Description :

4-in/4-out Audio/MIDI Interface with HDDA Mic Preamps and iOS Compatibility

TASCAM's US-4x4 combines great audio quality and ergonomic design for a powerful 4-in/4-out USB 2 audio interface.

Four of TASCAM's Ultra-HDDA mic/line preamps provide up to 57dB of gain with nearly inaudible noise and distortion specs. The audio design features high-performance, musical components like NE5532 op amps for rich sound quality without coloring the source.

The US-4x4 includes class-compliant drivers for plug-and-play operation on Mac OSX and iOS devices like the iPad, and a simple driver adds ASIO compatibility for Windows. MIDI in and out are also included for connecting

synths, drum machines, and controllers. The interface includes two DAW applications to choose from – both Cakewalk SONAR X3 LE and Ableton Live Lite 9.

With solid audio specs, iOS compatibility, and an easy-to-read angled design, the US-4×4 is the ultimate 4-channel interface for home, project, and mobile studios.

Product Gallery:



Customer Service Is Our Top Priority!