



Please Click On Product Title To Go To The Product Page To Purchase

TASCAM US-4X4 Computer-Tablet Audio Interface



	US - 4x4	
--	----------	--

Sampling frequency	44.1k/48k/88.2k/96kHz	
Quantization bit rate	16/24bit	
Analog audio inputs		
MIC IN	IN 1-4	
Connector	XLR-3-31(1:GND, 2:HOT, 3:COLD), BALANCED	
Input impedance	2.2k ohms	
Nominal input level		
GAIN:MAX	-65dBu (0.0004Vrms)	
GAIN:MIN	-8dBu (0.3090Vrms)	
Maximum input level (GAIN:MIN)	+8dBu (1.9467Vrms)	
Gain	57dB	
INST IN	IN 1-2	
Connector	6.3mm(1/4")TS-jack(T□HOT, S□GND), UNBALANCED (When set to "INST" at MIC/LINE.INST switch)	
Input impedance	1M ohms	
Nominal input level		
GAIN:MAX	-63dBV(0.0007Vrms)	
GAIN:MIN	-6dBV(0.5015Vrms)	
Maximum input level (GAIN:MIN)	+10dBV(3.162Vrms)	
Gain	57dB	
LINE IN	IN 1-4	

Connector	6.3mm(1/4")TRS-jack(T□HOT, R□COLD, S□GND), BALANCED (When set to "MIC/LINE" at MIC/LINE.INST switch)	
Input impedance	10k ohms	
Nominal input level		
GAIN:MAX	-53dBu(0.0017Vrms)	
GAIN:MIN	+4dBu(1.228Vrms)	
Maximum input level (GAIN:MIN)	+20dBu(7.75Vrms)	
Gain	57dB	
Analog audio outputs		
LINE OUT		
Connector	6.3mm(1/4")TRS-jack(T□HOT, R□COLD, S□GND), BALANCED	
Output impedance	110ohms	
Nominal output level	+4dBu (1.273Vrms)	
Maximum output level	+20dBu (7.75Vrms)	
PHONES		
Connector	6.3mm(1/4") stereo phone jack	
Maximum output level	45mW+45mW or more (THD+N 0.1% or less, 32ohms loaded)	
MIDI IN / OUT		
Connector	Din 5-pin	

Format	Standard MIDI format	
USB		
Connector	USB B type 4-pin	
Format	USB2.0 HIGH SPEED	
Power		
When connected PC		Dedicated AC adapter (GPE248-120200-Z, included)
When connected iOS		
Power consumption	5W	
Dimensions	11.62" W x 2.56" H x 6.3" D (296mm W x 65mm H x 160mm D)	
Weight	3.53lb (1.6kg)	
Operating temperature	5 to 35°C	
Bundled software	Cakewalk SONAR X3 LE Ableton Live 9 Lite	
Accessories	AC adapter(GPE248-120200-Z), USB cable, SONAR X3 LE license card, Live 9 Lite license card, User's manual, warranty card	

Audio performance	
Frequency response	
LINE OUT (BALANCED)	
44.1k/48k Hz	20Hz to 20kHz, +0dB/-0.1dB
88.2k/96k Hz	20Hz to 40kHz, +0dB/-0.2dB
PHONES	

44.1k/48k Hz	20Hz to 20kHz, +0dB/-0.5dB
88.2k/96k Hz	20Hz to 40kHz, +0dB/-2dB
THD	0.003% or less
S/N ratio	101dB or more
Crosstalk	95dB or more
EIN	-127dBu or less

Computer system

Windows	
OS	Windows 7(32-bit SP1, 64-bit SP1), Windows 8.0 or later of the late
Compatible computers	Windows-compatible
CPU type/speed	Dual-core
Memory	
DRIVER	

Macintosh

OS	OS X Mountain Lion(10.8), OS X Mavericks(10.9)*
Compatible computers	Apple Macintosh
CPU type/speed	Dual-core
Memory	
DRIVER	

iOS	
OS	iOS 7* For more information ab

UPC 043774031016

Price: \$249.99

SKU: 7000

Categories: [Audio Interfaces](#), [Recording Equipment](#)

Tags: [Computer Interface](#)

Product Short Description :

4-in/4-out Audio/MIDI Interface with HDDA Mic Preamps and iOS Compatibility

TASCAM's US-4×4 combines great audio quality and ergonomic design for a powerful 4-in/4-out USB 2 audio interface.

Four of TASCAM's Ultra-HDDA mic/line preamps provide up to 57dB of gain with nearly inaudible noise and distortion specs. The audio design features high-performance, musical components like NE5532 op amps for rich sound quality without coloring the source.

The US-4×4 includes class-compliant drivers for plug-and-play operation on Mac OSX and iOS devices like the iPad, and a simple driver adds ASIO compatibility for Windows. MIDI in and out are also included for connecting synths, drum machines, and controllers. The interface includes two DAW applications to choose from – both Cakewalk SONAR X3 LE and Ableton Live Lite 9.

With solid audio specs, iOS compatibility, and an easy-to-read angled design, the US-4×4 is the ultimate 4-channel interface for home, project, and mobile studios.

Product Gallery:



Customer Service Is Our Top Priority!