

# TASCAM US-4X4 Computer-Tablet Audio Interface



US-4x4

Sampling frequency  
Quantization bit rate  
Analog audio inputs

**MIC IN**

Connector  
Input impedance  
Nominal input level  
GAIN:MAX  
GAIN:MIN  
Maximum input level  
(GAIN:MIN )  
Gain

**INST IN**

Connector

Input impedance  
Nominal input level  
GAIN:MAX  
GAIN:MIN  
Maximum input level  
(GAIN:MIN )

IN 1-4  
XLR-3-31

IN 1-2  
6.3mm(1/4")  
(When set

|                       |                                                        |
|-----------------------|--------------------------------------------------------|
| Gain                  |                                                        |
| <b>LINE IN</b>        | IN 1-4                                                 |
| Connector             | 6.3mm(1/4") TRS<br>(When set to)                       |
| Input impedance       |                                                        |
| Nominal input level   |                                                        |
| GAIN:MAX              |                                                        |
| GAIN:MIN              |                                                        |
| Maximum input level   |                                                        |
| (GAIN:MIN )           |                                                        |
| Gain                  |                                                        |
| Analog audio outputs  |                                                        |
| <b>LINE OUT</b>       |                                                        |
| Connector             | 6.3mm(1/4") TRS                                        |
| Output impedance      |                                                        |
| Nominal output level  |                                                        |
| Maximum output level  |                                                        |
| PHONES                |                                                        |
| Connector             | 6.3mm(1/4") TRS                                        |
| Maximum output level  | 6.3mm(1/4") TRS<br>45mW+45mW o<br>(THD+N 0.1% or less, |
| MIDI IN / OUT         |                                                        |
| Connector             |                                                        |
| Format                |                                                        |
| USB                   |                                                        |
| Connector             |                                                        |
| Format                |                                                        |
| Power                 |                                                        |
| When connected PC     |                                                        |
| When connected iOS    |                                                        |
| Power consumption     |                                                        |
| Dimensions            | 5W<br>11.62" W x 2.56"<br>(296mm W x65mm H             |
| Weight                | 3.53lb (1.6                                            |
| Operating temperature |                                                        |
| Bundled software      |                                                        |

Accessories AC adapter(GPE248-120200-Z), USB cable, SONAR X3 LE license card

### Audio performance

Frequency response

**LINE OUT(BALANCED)**

44.1k/48k Hz 20Hz to 20kHz, +0dB/-0.1dB

88.2k/96k Hz 20Hz to 40kHz, +0dB/-0.2dB

**PHONES**

44.1k/48k Hz 20Hz to 20kHz, +0dB/-0.5dB

88.2k/96k Hz 20Hz to 40kHz, +0dB/-2dB

THD 0.003% or less

**S/N ratio** 101dB or more

Crosstalk 95dB or more

EIN -127dBU or less

### Computer system requirements

**Windows**

OS Windows 7(32-bit SP1, 64-bit SP1), Windows 8.0(32-bit, 64-bit),  
of the latest OS version, please click [here](#).

Compatible computers Windows-compatible computer with a USB 2.0 port

CPU type/speed Dual core/2 GHz or faster (x86)

|                      |                                                                  |
|----------------------|------------------------------------------------------------------|
| Memory               | 2GB or more                                                      |
| DRIVER               | ASIO2.0, WDM(MME)                                                |
| <b>Macintosh</b>     |                                                                  |
| OS                   | OS X Mountain Lion(10.8), OS X Mavericks(10.9)* For further info |
| Compatible computers | Apple Macintosh computer with a USB 2.0 port                     |
| CPU type/speed       | Dual core/2 GHz or faster                                        |
| Memory               | 2GB or more                                                      |
| DRIVER               | Core Audio, Core MIDI                                            |
| <b>iOS</b>           |                                                                  |
| OS                   | iOS 7* For more information about the OS compatibility on each m |
| UPC 043774031016     |                                                                  |