TASCAM US-2X2 Computer-Tablet Audio Interface

	US-2×2
Sampling frequency	44.1k/48k/88.
Quantization bit rate	16/24b
Analog audio inputs	
MIC IN	IN 1-2
Connector	XLR-3-31(1:GND, 2:HOT,
Input impedance	2.2k oh
Nominal input level	
GAIN:MAX	-65dBu (0.00
GAIN:MIN	-8dBu (0.309
Maximum input level (GAIN:MIN)	+8dBu (1.946
Gain	57dB
INST IN	IN 1-2
Connector	6.3mm(1/4″)TS-jack(T□HOT (When set to “INST” at MI
Input impedance	1M ohm
Nominal input level	

GAIN:MAX	-63dBV(0.000
GAIN:MIN	-6dBV(0.501
Maximum input level (GAIN:MIN)	+10dBV(3.16
Gain	57dB
LINE IN	IN 1-2
Connector	6.3mm(1/4″)TRS-jack(T□HOT, R (When set to “MIC/LINE” at
Input impedance	10k ohm
Nominal input level	
GAIN:MAX	-53dBu(0.001
GAIN:MIN	+4dBu(1.228
Maximum input level (GAIN:MIN)	+20dBu(7.75
Gain	57dB
Analog audio outputs	
LINE OUT	
Connector	6.3mm(1/4″)TRS-jack(T□HOT, R
Output impedance	110ohm
Nominal output level	+4dBu (1.27
Maximum output level	+20dBu (7.7
PHONES	
Connector	6.3mm(1/4″) stere
Maximum output level	18mW+18mW or more (THD+N 0.1% or less, 32ohms loaded)
MIDI IN / OUT	
Connector	Din 5-p
Format	Standard MIDI
USB	
Connector	USB B type
Format	USB2.0 HIGH
Power	
When connected PC	USB bus powered
When connected iOS	AC Adapter (TASCAM PS-P520, sold separately)
Power consumption	2.5W
Dimensions	7.32″ W ×2.56″ H ×6.3″ D (186mm W x 65mm H x 160mm D)
Weight	2.43lb (1.1kg)
Operating temperature	5 to 35
Bundled software	Cakewalk SONA Ableton Live
Accessories	USB cable, SONAR X3 LE license card, Live 9 Lite license card,

Audio performance

Frequency response	
LINE OUT(BALANCED)	
44.1k/48k Hz	20Hz to 20kHz, +0dB/-0.1dB
88.2k/96k Hz	20Hz to 40kHz, +0dB/-0.2dB
PHONES	
44.1k/48k Hz	20Hz to 20kHz, +0dB/-0.5dB
88.2k/96k Hz	20Hz to 40kHz, +0dB/-2dB
THD	0.003% or less
S/N ratio	101dB or more
Crosstalk	95dB or more
EIN	-127dBu or less

Computer system requirements

Windows

OS	Windows 7(32-bit SP1, 64-bit SP1), Windows 8.0(32-bit, 64-bit), of the latest OS version, please click here.
Compatible computers	Windows-compatible computer with a USB 2.0 port
CPU type/speed	Dual core/2 GHz or faster (x86)
Memory	2GB or more
DRIVER	ASIO2.0, WDM(MME)

Macintosh

OS	OS X Mountain Lion(10.8), OS X Mavericks(10.9)* For further info
Compatible computers	Apple Macintosh computer with a USB 2.0 port
CPU type/speed	Dual core/2 GHz or faster
Memory	2GB or more
DRIVER	Core Audio, Core MIDI

iOS

OS	iOS 7* For more information about the OS compatibility on each m

UPC 043774031009